This is a self-archived version of an original article. This version may differ from the original in pagination and typographic details.

Author(s): Vilén, Markus; Canete, Laetitia; Cheal, B.; Giatzoglou, A.; de Groote, Ruben; de Roubin, Antoine; Eronen, Tommi; Geldhof, Sarina; Jokinen, Ari; Kankainen, Anu; Moore, Iain; Nesterenko, Dmitrii; Penttilä, Heikki; Pohjalainen, Ilkka; Reponen, Mikael; Rinta-Antila, Sami

Title: A new off-line ion source facility at IGISOL

Year: 2020

Version: Accepted version (Final draft)

Copyright: © 2019 Elsevier B.V.

Rights: CC BY-NC-ND 4.0

Rights url: <https://creativecommons.org/licenses/by-nc-nd/4.0/>

Please cite the original version:

Vilén, M., Canete, L., Cheal, B., Giatzoglou, A., de Groote, R., de Roubin, A., Eronen, T., Geldhof, S., Jokinen, A., Kankainen, A., Moore, I., Nesterenko, D., Penttilä, H., Pohjalainen, I., Reponen, M., & Rinta-Antila, S. (2020). A new off-line ion source facility at IGISOL. *Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment*, 263, 382-383. <https://doi.org/10.1016/j.nimb.2019.04.051>

A new off-line ion source facility at IGISOL

M. Vilén^{a,*}, L. Canete^a, B. Cheal^b, A. Giatzoglou^c, R. de Groote^a, A. de Roubin^a, T. Eronen^a, S. Geldhof^a, A. Jokinen^a, A. Kankainen^a, I.D. Moore^a, D.A. Nesterenko^a, H. Penttilä^a, I. Pohjalainen^a, M. Reponen^a, S. Rinta-Antila^a

^a*University of Jyväskylä, P.O. Box 35, FI-40014 University of Jyväskylä, Finland*

^b*Department of Physics, University of Liverpool, Liverpool L69 7ZE, United Kingdom*

^c*Department of Physics and Astronomy, University College London, Gower Street, London WC1E 6BT, United Kingdom*

Abstract

An off-line ion source station has been commissioned at the IGISOL (Ion Guide Isotope Separator On-Line) facility. It offers the infrastructure needed to produce stable ion beams from three off-line ion sources in parallel with the radioactive ion beams produced from the IGISOL target chamber. This has resulted in improved feasibility for new experiments by offering reference ions for Penning-trap mass measurements, laser spectroscopy and atom trap experiments.

Keywords: Discharge ion source, surface ion source, IGISOL

s

1. A new ion source facility at IGISOL-4

In this contribution, we present the latest addition to the IGISOL-4 (Ion Guide Isotope Separator On-Line) facility [1], a new off-line ion source station, see figure 1. The new ion source infrastructure consists of an ion source setup located on the second floor of the experimental hall and a beamline connecting the new system to the main IGISOL mass separator. The ion source station is designed to accommodate three ion sources simultaneously, two sources in the horizontal branches of the vacuum system and one vertically mounted.

*Corresponding author

Email address: markus.k.vilen@student.jyu.fi (M. Vilén)

Figure 1: Internal structure of the new off-line ion source station (a) and the full station (b).

10 The new station houses electrostatic ion optics that can accept a beam from each of the three directions. Both ion sources presented in figure 1 utilize a skimmer electrode to form an ion beam which is injected into the quadrupole bender. The beam is focused with an Einzel lens, situated immediately after the quadrupole bender, and its alignment is adjusted using a set of steering
15 electrodes. The ions have $800qeV$ of energy, q being the charge state of the ions, before entering the extractor electrode which further accelerates them to $30q$ keV.

Subsequently, ions are transported to the lower floor of the IGISOL facility, deflected by 90° into the horizontal beamline and separated based on their m/q
20 ratio using a dipole magnet. The deflector system consists of two sets of parallel plates, one curved set of plates that deflects the ions by 65° and another set with straight plates that can be used to deflect the ions by the remaining 25° . The system can accept beam from either the off-line ion source station or the IGISOL target chamber. Switching between these two sources is achieved by
25 alternating a voltage on the latter set of parallel plates.

In its present configuration, the ion source station houses two types of ion source, a surface ion source based on resistive heating and a glow discharge ion source. The former ionizes a mixture of potassium, rubidium and cesium,

whereas the latter source is a more flexible device that ionizes its cathode material via electric discharge through helium buffer gas. The ion source station
30 is equipped with a cryogenic buffer gas purification system in order to provide beams with higher concentrations of the cathode material. Commissioning of a third ion source, a laser ablation ion source, is being planned.

2. Commissioning of the ion source station

35 After the first commissioning runs with ^{63}Cu and ^{133}Cs , the new ion source station has been employed in many experiments at IGISOL. The station was used to provide ion samples in parallel to the IGISOL system. This enabled the laser spectroscopy work [2] by making $^{89}\text{Y}^{2+}$ ions available where they would not have been previously and made possible the Penning trap mass measurement campaign [3] conducted fully off-line using both the vertical and horizontal
40 beamlines. Additionally, the ion source station has been used to provide well-known and identified reference ions for the on-line Penning trap mass measurements [4] and to provide $^{133}\text{Cs}^+$ for demonstrating the operation of a new laser cooling and trapping facility for the production of ultra-cold atomic samples of
45 caesium [5]. The new station has been proven to be a useful tool in preparing for on-line experiments through allowing initial tuning of both Penning trap and collinear laser systems without disrupting preparation of the IGISOL front end.

Operating parameters of the system were mostly the same during these experiments, with the exception of ion source settings. Typical values for the glow
50 discharge ion source were 5 – 10 mbar helium pressure and 800 – 1400 V source voltage. Current used to heat the surface ion source was adjusted based on the amount of beam needed, typically being 1.5 – 1.8 A.

3. Conclusions

The new ion source infrastructure has been used in several experiments
55 demonstrating additional flexibility in the operating modes of the IGISOL facility, enabling novel experiments, such as [2], and the possibility to conduct

Penning trap mass measurement campaigns in a fully off-line operating mode. The off-line ion source station, with its two commissioned ion sources, provides a large variety of mass separated ion beams to experiments. Commissioning
60 of a third ion source based on laser ablation would not only provide an increased number of ion species for experiments, but also a possibility to explore carbon cluster formation which would be of interest as reference ions for mass measurements.

References

- 65 [1] I. Moore, T. Eronen, D. Gorelov, J. Hakala, A. Jokinen, A. Kankainen, V. Kolhinen, J. Koponen, H. Penttilä, I. Pohjalainen, M. Reponen, J. Rissanen, A. Saastamoinen, S. Rinta-Antila, V. Sonnenschein, J. Äystö, [Towards commissioning the new IGISOL-4 facility](#), Nuclear Instruments and Methods in Physics Research Section B: Beam Interactions with Materials and Atoms
70 317 (2013) 208 – 213, xVith International Conference on ElectroMagnetic Isotope Separators and Techniques Related to their Applications, December 2–7, 2012 at Matsue, Japan (2013). doi:10.1016/j.nimb.2013.06.036.
URL <http://www.sciencedirect.com/science/article/pii/S0168583X13007143>
- 75 [2] L. J. Vormawah, M. Vilén, R. Beerwerth, P. Campbell, B. Cheal, A. Dicker, T. Eronen, S. Fritzsche, S. Geldhof, A. Jokinen, S. Kelly, I. D. Moore, M. Reponen, S. Rinta-Antila, S. O. Stock, A. Voss, [Isotope shifts from collinear laser spectroscopy of doubly charged yttrium isotopes](#), Phys. Rev. A 97 (2018) 042504 (Apr 2018). doi:10.1103/PhysRevA.97.042504.
80 URL <https://link.aps.org/doi/10.1103/PhysRevA.97.042504>
- [3] D. Nesterenko, L. Canete, T. Eronen, A. Jokinen, A. Kankainen, Y. Novikov, S. Rinta-Antila, A. de Roubin, M. Vilen, [High-precision measurement of the mass difference between \$^{102}\text{Pd}\$ and \$^{102}\text{Ru}\$](#) , International Journal of Mass Spectrometry 435 (2019) 204 – 208 (2019).

- 85 [doi:10.1016/j.ijms.2018.10.038](https://doi.org/10.1016/j.ijms.2018.10.038).
URL <http://www.sciencedirect.com/science/article/pii/S1387380618303257>
- [4] M. Vilén, J. M. Kelly, A. Kankainen, M. Brodeur, et.al, Exploring the mass surface near the rare-earth abundance peak via precision mass measurements, to be submitted.
90
- [5] A. Giatzoglou, T. Poomaradee, I. Pohjalainen, S. Rinta-Antila, I. D. Moore, P. M. Walker, L. Marmugi, F. Renzoni, [A facility for production and laser cooling of cesium isotopes and isomers](#), Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment 908 (2018) 367 – 375 (2018).
95 [doi:10.1016/j.nima.2018.08.095](https://doi.org/10.1016/j.nima.2018.08.095).
URL <http://www.sciencedirect.com/science/article/pii/S0168900218310532>